

BOWLING
NOW



BALL NAME PART NUMBER COLOR CORE COVERSTOCK RG MAX RG INT RG MIN DIFFERENTIAL ASYMMETRIC DIFF HOOK (1-185) LENGTH (1-235) BREAKPOINT (1-100) FACTORY FINISH	DV8 Reckless						
	60-105393-93X						
	Blue/Green Pearl	BACK OF BALL > <i>Guts or gutter</i> 					
	Reckless Core						
	Class 3 Reactive						
	2.573						
	2.572						
	2.523						
	0.050						
	0.001						
150							
110							
90							
500 Siaair Micro Pad/Rough Buff Finish							
	<i>16LB</i>	<i>15LB</i>	<i>14LB</i>	<i>13LB</i>	<i>12LB</i>	<i>11LB</i>	<i>10LB</i>
RG MAX	2.562	2.573	2.591	2.625	2.648	2.771	2.802
RG INT	2.561	2.572	2.590	2.624	2.647	2.770	2.801
RG MIN	2.512	2.523	2.541	2.585	2.608	2.769	2.800
RG DIFF	0.050	0.050	0.050	0.040	0.040	0.002	0.002
RG ASY	0.001	0.001	0.001	0.001	0.001	0.001	0.001

BALL MOTION

Finished with a Rough Buff Polish, the Reckless projects easily through the front part of the lane, revving hard in the mid-lane to create a very strong and continuous backend motion that drives through the pins on medium to medium oily lane conditions.

REACTION SETUP

The DV8 Reckless can be drilled using the standard drilling techniques developed for bowling balls with symmetric cores.

RECKLESS SPECS